Paragon High Speed Inkjet Plotter

Special Features

High-speed servo control, full closed loop positioning. Ink consumption tips, paperless alarm. Automatically record the location. Network connection automatically printed. Real-time monitoring of various operating conditions. Offline Storage Module (optional) Wireless Transition Module (optional).







| Characteristics | PN-165T | PN-185T | PN-205T | PN-225T | | | |
|---------------------------|---------|---|---------|---------|--|--|--|
| Printing Width | 165cm | 185cm | 205cm | 225cm | | | |
| Printing Speed | | 135m2/Hour(2-Head)240m2/Hour(4-Head) | | | | | |
| Speed Upgrade | | 3 Head &4 Head | | | | | |
| Print Head | | HP-45,HP-11 &HP-818 Nozzle | | | | | |
| Max. Weight of Paper Roll | | 37-45Kgs | | | | | |
| Print Density | | 300-600DPI(Optional Toner Save Mood) | | | | | |
| Paper Thickness | | 25-80GSM | | | | | |
| File Type Accepted | | DMPL, DXF, HPGL, PLT, PLX, Micro Jet STD Same | | | | | |
| Operating Option | | Digital Touch Pad / Key Type | | | | | |
| Paper Feeding System | | Front / Back side. | | | | | |
| Output System | | Take up mode / Drop on Floor | | | | | |
| Power | | 100V/220V,50Hz/60Hz,300W | | | | | |
| Working Environment | | 5-40 | | | | | |
| Interface | | USB 2.0 /NET Port | | | | | |

Paragon High Speed Inkjet Plotter

Special Features

High-speed servo control, full closed loop positioning. Ink consumption tips, paperless alarm. Automatically record the location. Network connection automatically printed. Real-time monitoring of various operating conditions. Offline Storage Module (optional) Wireless Transition Module (optional).







| Characteristics | PN-165T | PN-185T | PN-205T | PN-225T | | | |
|---------------------------|---------|---|---------|---------|--|--|--|
| Printing Width | 165cm | 185cm | 205cm | 225cm | | | |
| Printing Speed | | 135m2/Hour(2-Head)240m2/Hour(4-Head) | | | | | |
| Speed Upgrade | | 3 Head &4 Head | | | | | |
| Print Head | | HP-45,HP-11 &HP-818 Nozzle | | | | | |
| Max. Weight of Paper Roll | | 37-45Kgs | | | | | |
| Print Density | | 300-600DPI(Optional Toner Save Mood) | | | | | |
| Paper Thickness | | 25-80GSM | | | | | |
| File Type Accepted | | DMPL, DXF, HPGL, PLT, PLX, Micro Jet STD Same | | | | | |
| Operating Option | | Digital Touch Pad / Key Type | | | | | |
| Paper Feeding System | | Front / Back side. | | | | | |
| Output System | | Take up mode / Drop on Floor | | | | | |
| Power | | 100V/220V,50Hz/60Hz,300W | | | | | |
| Working Environment | | 5-40 | | | | | |
| Interface | | USB 2.0 /NET Port | | | | | |

1